



## FEATURES

- Multiple Progressive Scan CMOS Sensor Support 4M Resolution
- Quad Codec Support (H.264 Baseline / Main Profile / High Profile / MJPEG)
- Quad Streams Support
- On-Board Video Content Analytics
- IR LED Module Support (working distance up to 40m)
- Weatherproof (IP67 International)
- ONVIF Profile S/G Support

## TECHNICAL SPECIFICATION

Image Sensor	1/3" Progressive CMOS
Effective Pixels	4M (2688x1520)
Illumination	Color 0.1 lux@F1.2, B/W: 0.01 lux@F1.2
Shutter Speed	1 ~ 1/10000 sec.
S/N Ratio	>50 dB
LENS	Auto Focus, 2.8-12 mm focal length
<b>Network</b>	
Interface	RJ-45, 10/100 Mbps Ethernet
Video Compression	MJPEG / H.264 (MPEG-4 Part 10/AVC) Baseline / Main Profile / High Profile
<b>Image Setting</b>	
Iris Control	Auto / Manual
Backlight Compensation	On / Off
White Balance	Auto/Manual / ATW / One Push
Noise Reduction	3D / 2D / Color , Low / Middle / High / Off (W/Motion compensation)
Wide Dynamic Range	Shutter WDR On/Off (120dB)
Privacy Mask	On / Off
Digital Zoom	Support
ICR	Day / Night / Auto cut
Built-in Analytic	Abandoned Object, Intrusion Detection, Camera Sabotage, Wrong Direction, Loitering Detection, Object Counting, Object Removal, Stopped Vehicle

**Video Streaming**

Dual Streams	Normal Mode	H.264 4M (2688x1512) @25/30 fps + H.264 D1 @25/30 fps Note: One of the streamings (2M or under) can be set as MJPEG
	HDR Mode	H.264 4M (2688x1512) @25/30 fps + H.264 D1 @25/30 fps Note: One of the streamings (2M or under) can be set as MJPEG
Quad Streams	Normal Mode	H.264 4M(2688x1512) @25/30 fps + H.264 720P @25/30 fps + H.264 VGA @25/30 fps + H.264 CIF @25/30 fps Note: One of the streamings (2M or under) can be set as MJPEG
	HDR Mode	H.264 4M (2688x1512) @25/30 fps + H.264 720P @25/30 fps + H.264 VGA @25/30 fps + H.264 CIF @25/30 fps
Video Resolution	H.264	4M (2688x1512 or 2560x1440) / Full HD 1080P / SXGA / 720P / XGA / SVGA / D1 / VGA / CIF
	MJPEG	Full HD 1080P / SXGA / 720P / XGA / SVGA / D1 / VGA / CIF
Protocol	IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP, SNMP, QoS, ONVIF, unicast, multicast	
Security	HTTPS / IP Filter / IEEE 802.1X	
AudioInput	Line in	Max 6.2 Vpp for line signal Input Impedance: 33KΩ
	Microphone in	Max 1 Vpp for microphone Input impedance: 33KΩ
Password Levels	User and Administrator	
<b>Audio</b>		
Two-way Audio	Line in / Line Out	
Compression	G.711 / G.726 / AAC / LPCM	
<b>Mechanical</b>		
Built-in IR Illuminator	Working Distance up to 40 m	
LED Indicator	Power / ACT ; Status	

**General**

Operating Temperature	-30°C ~ 65°C w/Heater, powered by DC12V/AC24V/PoE: -50°C ~ 65°C
Humidity	10% ~ 90%, No Condensation
Weatherproof Standard	IP67
Dimension	Ø90x 220 mm (Ø 3.54 x 10.6 in.)
Weight	840 g (1.85 lb)
Power Source	DC 12V / AC 24V / PoE (802.3af)