



FEATURES

- HD IP Weather-proof Camera
- Plug and play tech(P2P)
- H.264/H.265 video encoding
- Support ONVIF2.0
- Offer CMS and Mobile APP
- Lens: 2.8-12mm HD lens
- IR Leds: 42pcs IR leds
- IR Range: 50m IR Range

TECHNICAL SPECIFICATION

TECHNICAL SPECIFICATION	
Type	HD IP Weather-proof Camera
Horizontal Resolution	4.0 Megapixel Super Low Lux
Solution	1/2.7" SONY290+3516CV30 0(WDR and Starlight)
Effective Pixels(HxV)	Main stream: 2288*1712 Deputy stream: 704*576
Mini illumination	0.01lux-sec
Frame Rate	4.0MP@25FPS
Network Port	1 RJ45 Ethernet interface, 10M/100M self-adaption
Network Protocol	TCP/UDP/HTTP/MULTICAST/UPnP/NTP/RTSP
ONVIF	Support Onvif 2.0
Lens	2.8-12mm HD lens
IR LEDs	42pcs IR leds
Night Vision	50Meter
Video Compression	H.264 / H.265 / JPEG
Mobile Phone Monitor	Support iPhone, Windows, Android mobile view
Motion Detect	YES
POE	YES

Operation Function	Offer free CMS, Support We etting, OSD, real-time video transmission, support motion eYbEfsoSdetection and IO alarm linkag r front end shortage/Capture/playback/download, Support Central remind and image linkage after motion detection and IO alarm linkage, support MJPEG capture, Support unit client-side remote management software
Operating Temperature	-10 ~ 50°C (relative humidity: max95%)
Power Voltage	DC12V±10% / POE (802.3af)
IP range	IP66
Material	Aluminum alloy
Weight	1.27kg
Dimension	255(L)x95(W)x150(H) mm